

ak



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
-----------------	-------------	----------------------	---------------------	------------------

10/770,116

02/02/2004

Giannakis B. Georgios

1008-022US01

9359

28863 7590 05/02/2007  
SHUMAKER & SIEFFERT, P. A.  
1625 RADIO DRIVE  
SUITE 300  
WOODBURY, MN 55125

EXAMINER

HUANG, DAVID S

ART UNIT

PAPER NUMBER

2609

MAIL DATE

DELIVERY MODE

05/02/2007

PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

## Office Action Summary

Application No.

10/770,116

Applicant(s)

GEORGIOS ET AL.

Examiner

David Huang

Art Unit

2609

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 02 February 2004.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1-42 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-42 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☒ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some \* c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
  - ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO/SB/08)  
Paper No(s)/Mail Date See Continuation Sheet.
- 4) ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date. \_\_\_\_\_.
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: \_\_\_\_\_.

Continuation of Attachment(s) 3). Information Disclosure Statement(s) (PTO/SB/08), Paper No(s)/Mail Date :9/13/2004, 8/22/2005, 2/27/2006.

## DETAILED ACTION

### *Information Disclosure Statement*

1. The references listed in the Information Disclosure Statements filed on September 13, 2004, August 22, 2005, and February 27, 2006 have been considered by the examiner (see attached PTO-1449 form or PTO/SB/08A and 08B forms.

### *Oath/Declaration*

2. The oath or declaration is defective. A new oath or declaration in compliance with 37 CFR 1.67(a) identifying this application by application number and filing date is required. See MPEP §§ 602.01 and 602.02.

The oath or declaration is defective because:  
It does not identify the citizenship of each inventor.

### *Claim Objections*

3. **Claim 40** is objected to because of the following informalities: the step of “generating **an** outbound streams” is confusing and should be revised to clarify how many outbound streams are generated. Appropriate correction is required.

### *Claim Rejections - 35 USC § 101*

4. 35 U.S.C. 101 reads as follows:

Whoever invents or discovers any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof, may obtain a patent therefor, subject to the conditions and requirements of this title.

**Claim 42** is rejected under 35 U.S.C. 101 because the claimed invention is directed to non-statutory subject matter. The preamble lacks the proper form for a computer program product and therefore is not a process, machine, manufacture, or composition of matter.

Examiner suggests the following correction to the claim language of the preamble:

“A computer-readable medium encoded with computer executable instructions for causing a programmable processor of a wireless communication device...”

***Claim Rejections - 35 USC § 112***

5. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

6. **Claims 10, 11, and 34** are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

7. **Claim 10** recites the limitation "power splitter" in line 1. There is insufficient antecedent basis for this limitation in the claim.

8. **Claim 11** recites the limitation "space-time coded data streams" in line 2. There is insufficient antecedent basis for this limitation in the claim.

9. **Claim 34** recites the limitation "stream of symbols" in lines 1-2, and the limitation "constellation selector" in line 2. There is insufficient antecedent basis for these limitations in the claim. The parent claim -claim 30- does not contain either limitation, but claim 31 introduces the "data stream of symbols" limitation in line 2. The "constellation selector" is interpreted to refer to the step of adaptively selecting a signal constellation in parent claim 30.

***Claim Rejections - 35 USC § 103***

10. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

11. **Claims 1, 2, 4, 11-14, 17-18, 21, 23, 24, 30-33, 40-42** are rejected under 35 U.S.C. 103(a) as being unpatentable over Ling et al. (US Patent Application Publication 2002/0191703) in view of Onggosanusi et al. (US Patent Application Publication 2002/0114269).

Regarding **claim 1**, Ling et al. disclose a wireless communication device comprising:

a constellation selector (symbol mapping element 208, Figure 2A) that adaptively selects a signal constellation from a set of constellations based on channel state information for a wireless communication channel, wherein the constellation selector maps information bits of an outbound data stream to symbols drawn from the selected constellation to produce a stream of symbols (Page 4, [0039]);

a MIMO processor (120a, Figure 2) that generates a plurality of coded data streams from the stream of symbols (page 4, [0041]); and

a plurality of transmit antennas that output waveforms in accordance with the plurality of coded data streams (page 4, [0041]; 124a-124t, Figure 2A).

However, Ling et al. fail to expressly disclose a beamformer.

Onggosanusi et al. teach disclose single stream transmitter module 18 coupled to channel state processing unit 16, which additionally incorporates sub-channel selection circuitry 24 containing beamformer weight determiner 30. The set of beamformer weights are passed on to the single stream transmitter module 18. The modulated signal stream is weighted by the corresponding value from the weight vector (page 3, [0043], [0045]; Figures 1 and 2).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide Ling et al. with the single stream transmitter module 18 and beamformer weight determiner as taught by Onggosanusi et al. because space-time beamformer

Art Unit: 2609

technology accounts for inter-symbol interference and is used to enhance signal transmissions (page 1, [0011]).

Regarding **claim 2**, Ling et al. disclose everything claimed as applied above (see *claim 1*), and further disclose wherein the constellation selector selects the signal constellation based at least in part on partial information (SNR) for the wireless communication channel (page 4, [0039]).

Regarding **claim 4**, Ling et al. disclose everything claimed as applied above (see *claim 1*), and further disclose wherein the constellation selector selects the signal constellation based at least in part on a target throughput (bit rate matches transmission capability, page 11, [0134]).

Regarding **claim 11**, the combination of Ling et al. and Onggosanusi et al. discloses everything claimed as applied above (see *claim 1*), and Onggosanusi et al. further disclose wherein the beamformer applies an antenna weighting vector to the space-time coded data streams to allocate a portion of each of the space-time coded data streams to each of the output antennas (page 3, [0045]).

Regarding **claim 12**, the combination of Ling et al. and Onggosanusi et al. discloses everything claimed as applied above (see *claim 11*), but fails to expressly disclose wherein the beamformer adaptively adjusts the antenna weighting vector based on the channel state information.

Onggosanusi et al. further teach in connection with selecting a sub-channel, a frequency index is selected and a corresponding set of beamformer weights are determined, both of which are respectively identified by a frequency index selector 29 and a beamformer weight determiner 30. The sub-channels are typically selected based upon the sub-channel having preferred

signaling characteristics as determined through an analysis of the channel state information (page 3, [0043]; Figure 1). These are contained in the sub-channel selection circuit 24, which is coupled to the channel state information estimator 20, which identifies a set of available orthogonal sub-channels within the channel space by analyzing the inherent gain associated with each signal path between each of a set of one or more transmit antennas 14 and each of a set of one or more corresponding receive antennas 22, as shown in Figure 4 (page 3, [0042], Figure 1).

Therefore it would have been obvious to one of ordinary skill in the art to modify the combination of applied to claim 11 to adjust the antenna weighting vector based on the channel state information since by carefully computing or selecting the sets of values from which the beamformer vector and the frequency index are selected, substantially orthogonal and/or non-interfering sub-channels can be defined (page 3, [0041]). This facilitates space-time beamformer technology, which accounts for inter-symbol interference and is used to enhance signal transmissions (page 1, [0011]).

Regarding **claim 13**, Ling et al. discloses everything claimed as applied above (see *claim 12*), but fails to expressly disclose wherein the antenna weighting vector comprises an eigen vector of a correlation matrix representative of the channel state information.

Onggosanusi et al. disclose matrix  $H$ , which represents the overall channel (page 5, [0062]). The specific orthogonal vectors corresponding to the non-interfering sub-channels can be determined by computing the value of the signal value decomposition of matrix  $H$ . The resulting inherently orthogonal eigenvectors can then be used to derive the set of appropriate weights for forming the necessary beamformer vectors for transmitting and receiving signals via the orthogonal sub-channels (page 5, [0066]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the combination applied in claim 12 with the teaching of Onggosanusi et al. because the analysis of the matrix  $H$  determines the number of orthogonal space-time dimensions, which correspond to the number of available non-interfering sub-channels (page 5, [0062]). This facilitates space-time beamformer technology, which accounts for inter-symbol interference and is used to enhance signal transmissions (page 1, [0011]).

Regarding **claim 14**, Ling et al. discloses everything claimed as applied above (see *claim 1*), but fail to expressly disclose wherein the beamformer is a two-dimensional beamformer that generates the plurality of coded data streams as two orthogonal data streams.

Onggosanusi et al. disclose multiple single stream transmitter modules 18 could be coupled in parallel. Each single stream transmitter module 18 would receive its own frequency index and set of beamformer weights corresponding to the unique sub-channel selected and receive a unique data stream for transmission (page 3, [0044]; Figure 1). This teaching is advantageous since facilitates a general multi-user transmitter (page 13, [0159], Figure 24).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide Ling et al. with multiple (two) single stream transmitter modules 18 as taught by Onggosanusi, since it would allow multiple (two) users to send data simultaneously.

Regarding **claim 17**, Ling et al. disclose a wireless communication device comprising:  
a plurality of adaptive modulators (TX data processor 114a-114k, Figure 4) to process respective streams of information bits (channel data stream, page 6, [0065]), wherein each adaptive modulators comprises:

(i) a constellation selector (symbol mapping element 208, Figure 2A) that adaptively selects a signal constellation from a set of constellations based on channel state information for a wireless communication channel, wherein the constellation selector maps the respective information bits to symbols drawn from the selected constellation to produce a stream of symbols (Page 4, [0039]); and

(ii) a MIMO processor (120d, Figure 4) that generates a plurality of coded data streams ( $V_1$ - $V_T$ , Figure 4) from the stream of symbols ( $S_1$ - $S_K$ , page 6, [0067]); and a modulator (122a to 122t, Figure 3) to produce a multi-carrier output waveform in accordance with the plurality of coded data streams ( for transmission through the wireless communication channel (page 6, [0060]-[0061], Figure 3).

However, Ling et al. fail to expressly disclose a beamformer.

Onggosanusi et al. teach disclose single stream transmitter module 18 coupled to channel state processing unit 16, which additionally incorporates sub-channel selection circuitry 24 containing beamformer weight determiner 30. The set of beamformer weights are passed on to the single stream transmitter module 18. The modulated signal stream is weighted by the corresponding value from the weight vector (page 3, [0043], [0045]; Figures 1 and 2).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide Ling et al. with the single stream transmitter module 18 and beamformer weight determiner as taught by Onggosanusi et al. in order to account for inter-symbol interference and to enhance signal transmissions (page 1, [0011]).

Art Unit: 2609

Regarding **claim 18**, Ling et al. disclose everything claimed as applied above (see *claim 17*), and further disclose a plurality of transmit antennas that output the multi-carrier waveform (antennas 124a to 124t, Figure 3, page 6, [0062]).

Regarding **claim 21**, Ling et al. disclose everything claimed as applied above (see *claim 17*), and further disclose wherein the constellation selectors (symbol mapping element 208, Figure 2A) of the adaptive modulators load additional information bits within the streams of information bits to indicate the selected constellations (the number of information bits that may be transmitted for each modulation symbol is dependent on the SNR of the transmission channel, Page 4, [0039]).

Regarding **claim 23**, Ling et al. disclose everything claimed as applied above (see *claim 17*), and further disclose wherein the adaptive modulators (symbol mapping element 208, Figure 2A) jointly perform power and bit loading across the streams of information bits (page 4, [0039]; groups sets of coded bits to form non-binary symbols, and maps the non-binary symbols into points in a signal constellation corresponding to a particular modulation scheme selected for that transmission channel, and the number of information bits that may be transmitted for each modulation symbol is dependent on the SNR of the transmission channel).

Regarding **claim 24**, Ling et al. disclose everything claimed as applied above (see *claim 17*), and further disclose wherein the constellation selectors of the adaptive modulators select the signal constellation for the respective stream of information bits based on partial information (SNR) for the wireless communication channel (page 4, [0039]).

Regarding **claim 30**, Ling et al. disclose a method comprising:

receiving channel state information for a wireless communication system (full or partial CSI reported by the receiver system, page 5, [0053]);

adaptively selecting a signal constellation from a set of constellations based on the channel state information (modulation adjusted based on available CSI, on Page 5, [0053]); and

coding signals for transmission by a multiple antenna transmitter based on the estimated channel information and the selected constellation (page 5, [0053]; page 4, [0040]; and Table 1).

Regarding **claim 31**, Ling et al. disclose everything claimed as applied above (see *claim 30*), and further disclose the method further comprising:

mapping information bits of an outbound data stream to symbols drawn from the selected constellation to produce a stream of symbols (page 6, [0065]);

generating a plurality of coded data streams from the stream of symbols to produce a plurality of coded signals (page 6, [0065]-[0066]); and

outputting waveforms from a plurality of transmit antennas (124a-124t, Figure 3) in accordance with the plurality of coded data streams (page 6, [0067]).

Regarding **claim 32**, Ling et al. disclose everything claimed as applied above (see *claim 31*), and further disclose wherein adaptively selecting a signal constellation comprises adaptively selecting the signal constellation based at least in part on channel mean feedback received from a second wireless communication device (page 6, [0068]).

Regarding **claim 33**, Ling et al. disclose everything claimed as applied above (see *claim 30*), and further disclose wherein coding signals comprises forming Eigen-beams based on the channel state information (eigenmodes are derived and applied, page 5, [0055]).

Regarding **claim 40**, Ling et al disclose everything claimed as applied above (see *claim 30*), and further disclose the steps:

adaptively selecting a signal constellation from a set of constellations for each sub-carrier of a multi-carrier wireless communication system (each frequency subchannel, page 6, [0066]);

generating an outbound streams for each sub-carrier based on the selected constellations ( $V_1$ - $V_T$ , Page 5, [0059], Figure 3); and

applying modulators (122, Figure 3) to produce a multi-carrier output waveform in accordance with the plurality of coded data streams for transmission through the multi-carrier wireless communication channel (page 6, [0060]-[0061]).

However, Ling et al. fail to expressly disclose the step of applying an eigen-beamformer to each of the streams of symbols to generate a plurality of coded data streams.

Onggosanusi et al. teach disclose single stream transmitter module 18 coupled to channel state processing unit 16, which additional incorporates sub-channel selection circuitry 24 containing beamformer weight determiner 30. The set of beamformer weights are passed on to the single stream transmitter module 18. The modulated signal stream is weighted by the corresponding value from the weight vector (page 3, [0043], [0045]; Figures 1 and 2).

Onggosanusi et al. also disclose matrix  $H$ , which represents the overall channel (page 5, [0062]). The specific orthogonal vectors corresponding to the non-interfering sub-channels can be determined by computing the value of the signal value decomposition of matrix  $H$ . The resulting inherently orthogonal eigenvectors can then be used to derive the set of appropriate weights for forming the necessary beamformer vectors for transmitting and receiving signals via the orthogonal sub-channels (page 5, [0066]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Ling et al. with the teaching of Onggosanusi et al. because it would facilitate space-time beamformer technology, which accounts for inter-symbol interference and is used to enhance signal transmissions (page 1, [0011]).

Regarding **claim 41**, Ling et al. disclose everything claimed as applied above (see *claim 40*), but fail to expressly disclose adaptively selecting a signal constellation for each subcarrier based on the power allocated to each subcarrier.

Onggosanusi et al. teach throughput is maximized by using all the  $N_{\text{dim}}$  spatio-temporal dimensions for data transmission as discussed above. However, for a fixed total transmitted power, this comes at the expense of BER since the power has to be distributed between  $N_{\text{dim}}$  streams. Hence there is a trade-off between throughput and BER. Throughput may be traded for lower BER by choosing to transmit with  $M < N_{\text{dim}}$  data streams. Since perfect CSI is available at the transmitter, the sub-channel gains (eigenvalues) can be determined (page 9, [0112]). The most power efficient way to achieve a relative throughput of  $M$  is to use the  $M$  sub-channels with the highest gains (page 9, [0013]). Since the sub-channel gains are determined based on CSI, the power allocation is also based on CSI.

Therefore, it would have been obvious to one of ordinary skill in the art to adaptively select a signal constellation based on the power allocated since there is a tradeoff between throughput and BER, and in order to maintain a minimum BER for a fixed total transmitted power, throughput may be reduced by choosing a lower modulation level.

Regarding **claim 42**, Ling et al. disclose a computer-readable medium comprising instructions for causing a programmable processor (page 12, [0143]) of a wireless communication device to:

receive channel state information for a wireless communication system (full or partial CSI reported by the receiver system, page 5, [0053]);

select a signal constellation from a set of constellations based on the channel state information (modulation adjusted based on available CSI, on Page 5, [0052]-[0053]); and

map information bits of an outbound data stream to symbols drawn from the selected constellation to produce a stream of symbols (page 6, [0065]).

However, Ling et al. fail to expressly disclose applying an eigen-beamformer to generate a plurality of coded data streams from the stream of symbols to produce a plurality of coded signals.

Onggosanusi et al. teach disclose single stream transmitter module 18 coupled to channel state processing unit 16, which additionally incorporates sub-channel selection circuitry 24 containing beamformer weight determiner 30. The set of beamformer weights are passed on to the single stream transmitter module 18. The modulated signal stream is weighted by the corresponding value from the weight vector (page 3, [0043], [0045]; Figures 1 and 2).

Onggosanusi et al. also disclose matrix  $H$ , which represents the overall channel (page 5, [0062]). The specific orthogonal vectors corresponding to the non-interfering sub-channels can be determined by computing the value of the signal value decomposition of matrix  $H$ . The resulting inherently orthogonal eigenvectors can then be used to derive the set of appropriate weights for

forming the necessary beamformer vectors for transmitting and receiving signals via the orthogonal sub-channels (page 5, [0066]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify Ling et al. with the teaching of Onggosanusi et al. because it would facilitate space-time beamformer technology, which accounts for inter-symbol interference and is used to enhance signal transmissions (page 1, [0011]).

12. **Claim 3** is rejected under 35 U.S.C. 103(a) as being unpatentable over Ling et al. (US Patent Application Publication 2002/0191703) in view of Onggosanusi et al. (US Patent Application Publication 2002/0114269) as applied to claim 1 above, and further in view of Visotsky et al. (NPL – *Space-Time Transmit Precoding with Imperfect Feedback*, September 2001).

Regarding **claim 3**, the combination of Ling et al. and Onggosanusi et al. discloses everything claimed as applied above (see *claim 1*), but fails to expressly disclose wherein the constellation selector selects the signal constellation based at least in part on channel mean feedback received from a second wireless communication device.

Visotsky et al. discloses two feedback schemes mean feedback and covariance feedback (Page 2633, Part B). For transmit antenna arrays, the gain through even partial knowledge of the channel can be substantial. For mean feedback, the beamforming strategy performs close to the optimal strategy when the feedback is of reasonable quality. The beamforming strategy performs close to the optimal strategy for covariance feedback when there is a strong path present which can be exploited by the beamforming. Overall, the beamforming strategy appears to be a viable

Art Unit: 2609

transmission strategy when meaningful feedback is present (page 2637, Section V, 1<sup>st</sup> paragraph).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide the combination applied to claim 1 with mean feedback since it provides the channel state information required to facilitate beamforming and the beamforming performs close to the optimal strategy when the mean feedback is of reasonable quality.

13. **Claims 5-8, 10, 16, 25, 26, 27, 29, and 34-36, 38-39** are rejected under 35 U.S.C. 103(a) as being unpatentable over Ling et al. (US Patent Application Publication 2002/0191703) in view of Onggosanusi et al. (US Patent Application Publication 2002/0114269) as applied to claim 1 above, and further in view of Dabak et al. (US Patent 6,594,473).

Regarding **claims 5 and 25**, Ling et al. disclose everything claimed as applied above (see *claims 1 and 17*), but fail to explicitly disclose wherein the beamformer (of each of the adaptive modulators) comprises a space-time block coder that processes the stream of symbols from the constellation selector to generate space-time block coded data streams.

Dabak et al. discloses open and closed loop encoder 60 which may be included within a transmitter such as transmitter 42 (Figure 4). Open loop diversity is depicted in Figure 2, as providing space time block coded transmit antenna diversity (STTD) (column 5, lines 46-52; Figure 2). Encoder 60 has an input 62, which by way of example is shown to receive a first symbol S<sub>1</sub> at a time T follow by a second symbol S<sub>2</sub> at a time 2T, and again assume by way of example that symbols S<sub>1</sub> and S<sub>2</sub> are QPSK symbols. Encoder 60 has two outputs 64<sub>1</sub> and 64<sub>2</sub>, each connected to a respective antenna A60<sub>1</sub> and A60<sub>2</sub> (column 13, lines 35-43; Figure 5). This teaching is advantageous because instances may arise where a transmitter in a closed loop

Art Unit: 2609

diversity system receives feedback from a receiver to develop weights for future transmissions, but due to some factor (e.g., high Doppler), the transmitter is informed of some reduced amount of confidence in the weights. A combined diversity system can be created by adding an open loop diversity technique (STTD) to the closed loop system (column 13, lines 24-33).

Therefore it would have been obvious to one of ordinary skill in the art, at the time the invention was made to provide Ling et al. with the encoder taught by Dabak et al. since open loop systems provide greater performance in a high Doppler environment (column 6, lines 38-41).

Regarding **claim 6**, the combination applied to *claim 5* further discloses in Dabak et al. wherein the space-time block coder processes the stream of symbols to generate N space-time block coded data streams, where N equals the number of transmit antennas (column 13, lines 42-43, see Figure 5).

Regarding **claim 7**, Ling et al. disclose everything claimed as applied above (see *claim 5*), but fails to expressly disclose wherein the beamformer comprises a power splitter that controls a total power allocated across the space-time block coded data streams.

Onggosanusi et al. disclose transmit power allocator 26 (Figure 1), coupled to channel state information estimator 20. The signal strength of the stream of data 12 has been modulated by a power amplification factor determined by the transmit power allocator 26 as part of the channel state processing unit 16 (page 3, [0042]-[0043]). This teaching is advantageous since for a fixed total transmitted power, there is a trade-off between throughput and BER (page 9, [0112]), and the power allocator 26 can be used to balance throughput and BER according to a desired performance level.

Art Unit: 2609

Therefore it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide Ling et al. with the transmit power allocator taught by Onggosanusi et al. because it would allow the system to balance achieving high throughput with sufficiently low BER.

Regarding **claim 8**, the combination applied to *claim 7* further discloses in Onggosanusi et al. wherein the power splitter adjusts the power allocated to the space-time block coded streams based at least in part on the channel information (transmit power allocator 26 coupled to channel state information estimator 20).

Regarding **claim 10**, Ling et al. disclose everything claimed as applied above (see claim 7), but fail to expressly disclose wherein the power splitter adjusts a power allocation of the data streams to maximize the transmission rate while maintaining a target bit error rate (BER).

Onggosanusi et al. disclose a strategy to maximize the instantaneous throughput from a given worst-case BER requirement (page 9, [0115]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the combination applied to *claim 7* to balance maximizing throughput with low BER as taught by Onggosanusi et al. since maintaining a minimum BER ensures proper transmission and reception of the information stream, whereas coding may not be able to correct of overly high BER.

Regarding **claims 16 and 29**, Ling et al. disclose everything claimed as applied above (see *claims 1 and 17*), but fail to explicitly disclose wherein the wireless communication device comprises a base station.

However, it is well known in the art to implement a transmitter with multiple antennas as a base station as is evidenced by Dabak et al. (column 8, lines 18-31, Figure 4).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to implement the wireless communication device as a base station since it is well known in the art.

Regarding **claim 26**, Ling et al. disclose everything claimed as applied to *claim 25*, and further disclose wherein the beamformer of each of the adaptive modulators comprises a power splitter that controls a total power allocated across the space-time block coded data streams based on the channel information.

Onggosanusi et al. disclose transmit power allocator 26 (Figure 1), coupled to channel state information estimator 20 (i.e., 26 receives channel state information from 20). The single stream transmitter module 18 additionally receives a stream of data 12, after the signal strength of the stream of data 12 has been modulated by a power amplification factor. The power amplification factor is determined by the transmit power allocator 26 as part of the channel state processing unit 16 (page 3, [0042]-[0043]). This teaching is advantageous since for a fixed total transmitted power, there is a trade-off between throughput and BER (page 9, [0112]). Thus, the power allocator 26 can be used to balance throughput and BER according to a desired performance level.

Therefore it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide Ling et al. with the transmit power allocator coupled to channel state information estimator taught by Onggosanusi et al. because they would allow the system to balance achieving high throughput with sufficiently low BER.

Regarding **claim 27**, the combination of Ling et al., Onggosanusi et al. and Dabak et al. discloses everything claimed as applied above (see *claim 25*), and Onggosanusi et al. further disclose wherein the beamformer of each of the adaptive modulators that applies an antenna weighting vector to the space-time coded data streams based on the channel state information to allocate a portion of each of the space-time coded data streams to each of the output antennas. (page 3, [0045]).

Regarding **claim 34**, Ling et al. disclose everything claimed as applied to *claim 30*, but fail to expressly disclose wherein coding signals comprises processing the stream of symbols from the constellation selector to generate space-time block coded data streams.

Dabak et al. discloses open and closed loop encoder 60 which may be included within a transmitter such as transmitter 42 (Figure 4). Open loop diversity is depicted in Figure 2, as providing space time block coded transmit antenna diversity (STTD) (column 5, lines 46-52; Figure 2). Encoder 60 has an input 62, which by way of example is shown to receive a first symbol  $S_1$  at a time  $T$  follow by a second symbol  $S_2$  at a time  $2T$ , and again assume by way of example that symbols  $S_1$  and  $S_2$  are QPSK symbols. Encoder 60 has two outputs  $64_1$  and  $64_2$ , each connected to a respective antenna  $A60_1$  and  $A60_2$  (column 13, lines 35-43; Figure 5). This teaching is advantageous because instances may arise where a transmitter in a closed loop diversity system receives feedback from a receiver to develop weights for future transmissions, but due to some fact (e.g., high Doppler), the transmitter is informed of some reduced amount of confidence in the weights. A combined diversity system can be created by adding an open loop diversity technique (STTD) to the closed loop system (column 13, lines 24-33).

Therefore it would have been obvious to one of ordinary skill in the art, at the time the invention was made to provide Ling et al. with the encoder taught by Dabak et al. since the open loop system provides greater performance in a high Doppler environment (column 6, lines 38-41).

Regarding **claim 35**, Ling et al. disclose everything claimed as applied to *claim 34*, but fail to expressly disclose the step of applying a power splitter to controls a total power allocated across the space-time block coded data streams.

Onggosanusi et al. disclose transmit power allocator 26 (Figure 1), coupled to channel state information estimator 20. The single stream transmitter module 18 additionally receives a stream of data 12, after the signal strength of the stream of data 12 has been modulated by a power amplification factor. The power amplification factor is determined by the transmit power allocator 26 as part of the channel state processing unit 16 (page 3, [0042]-[0043]). This teaching is advantageous since for a fixed total transmitted power, there is a trade-off between throughput and BER (page 9, [0112]). Thus, the power allocator 26 can be used to balance throughput and BER according to a desired performance level.

Therefore it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide Ling et al. with the transmit power allocator taught by Onggosanusi et al. because it would allow the system to balance achieving high throughput with sufficiently low BER.

Regarding **claim 36**, the combination applied to *claim 35* further discloses in Onggosanusi et al. adjusting the power allocated to the space-time block coded streams based at

least in part on the channel information (transmit power allocator 26 coupled to channel state information estimator 20).

Regarding **claim 38**, the combination applied to *claim 35* fails to disclose the step of applying an antenna weighting vector to the space-time coded data streams to allocate a portion of each of the space-time coded data streams to each of the multiple antennas.

Onggosanusi et al. disclose the modulated signal stream is coupled to each of the transmit antennas after being appropriately weighted by the corresponding value from the weight vector. Where multiple single stream transmitter modules 18 are used, each of the weighted signal streams for a particular antenna 14 are summed together before being coupled to the corresponding antenna 14 (page 3, [0045]; see Figures 1 and 2).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide the combination applied to claim 35 with the step of weighting as taught by Onggosanusi et al. because it would facilitate space-time beamformer technology which accounts for inter-symbol interference and is used to enhance signal transmissions (page 1, [0011]).

Regarding **claim 39**, the combination applied to *claim 38* fail to explicitly disclose the step of adjusting the antenna weighting vector based on the channel state information.

However it is implicit from Onggosanusi et al.'s disclosure that beamformer weight determiner 30 adjusts weights based on channel state information since sub-channel selection circuitry 24, which contains beamformer weight determiner 30, is coupled to the channel state information estimator 20. Sub-channels are selected based upon the sub-channel having preferred signaling characteristics as determined through an analysis of the channel state

Art Unit: 2609

information. In connection with selecting a sub-channel, a corresponding set of beamformer weights are determined (page 3, [0042]-[0043]; Figure 1).

14. **Claims 9 and 37** rejected under 35 U.S.C. 103(a) as being unpatentable over Ling et al. (US Patent Application Publication 2002/0191703) in view of Onggosanusi et al. (US Patent Application Publication 2002/0114269) and Dabak et al. (US Patent 6,594,473) as applied to *claims 8 and 35* above, and further in view of Sampath (US Patent Application Publication 2003/0043929).

Regarding **claim 9**, the combination applied to *claim 8* fails to expressly disclose wherein the power splitter adaptively adjusts allocation of total power across the space-time coded data streams as a function of the constellation that is selected by the constellation selector.

Sampath teaches if a first symbol stream includes a higher transmission order (higher order QAM) than a second symbol stream, the preprocessor can allocate more power to the first stream and less power to the second stream (page 5, [0069]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the combination applied to *claim 8* so that the power allocation is based on the chosen modulation order as taught by Sampath since input symbol streams can be scaled in this way to maximize the minimum distance between coded symbol streams.

Regarding **claim 37**, the combination applied to *claim 35* fails to expressly disclose the step of adaptively adjusting allocation of total power across the space-time coded data streams as a function of the constellation that is selected by the constellation selector.

Sampath teaches if a first symbol stream includes a higher transmission order (higher order QAM) than a second symbol stream, the preprocessor can allocate more power to the first stream and less power to the second stream (page 5, [0069]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the combination applied to *claim 8* so that the power allocation is based on the chosen modulation order as taught by Sampath since input symbol streams can be scaled in this way to maximize the minimum distance between coded symbol streams.

15. **Claims 15 and 28** are rejected under 35 U.S.C. 103(a) as being unpatentable over Ling et al. (US Patent Application Publication 2002/0191703) in view of Onggosanusi et al. (US Patent Application Publication 2002/0114269) as applied to *claims 1 and 17* above, and further in view of Hockley, Jr. et al. (US Patent Application Publication 2004/0008138).

Regarding **claims 15 and 28**, Ling et al. disclose everything claimed as applied above (see claims 1 and 17), but fail to explicitly disclose wherein the wireless communication device comprises a mobile phone.

Hockley, Jr. et al. disclose a mobile device 110 and although one antenna 210 is shown, a mobile device may implement more than one antenna (page 4, [0045], Figure 2). Furthermore, Hockley, Jr. et al. disclose the mobile device is a cellular phone (page 3, [0032]).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to specify the multiple antenna invention of Ling et al. to be a cellular phone since Hockley, Jr. et al. teach that a cellular phone or other mobile device may implement more than one antenna where each antenna may operate in a distinct frequency spectrum, or the multiple antennas may operate in overlapping frequency spectrums (page 4, [0045]).

Art Unit: 2609

16. **Claims 19-20** rejected under 35 U.S.C. 103(a) as being unpatentable over Ling et al. (US Patent Application Publication 2002/0191703) in view of Onggosanusi et al. (US Patent Application Publication 2002/0114269) as applied to *claim 17* above, and further in view of Heo et al. (US Patent Application Publication 2003/0103481).

Regarding **claim 19**, Ling et al. disclose everything claimed as applied above (see *claim 17*), but fail to expressly disclose wherein each adaptive modulator further comprises: a power loader that processes the respective stream of information bits and loads additional information bits indicative of a power allocated to the respective stream of information bits,

wherein the respective constellation selector adaptively selects the signal constellation based on based on the additional information bits.

Heo et al. discloses a control information generator for generating control information inserting at least one bit indicating a modulation order used for transmission of the spread packet among the a plurality of available modulation orders into one information field in the control information (Page 3, [0027]). The base station determines the modulation order to be used for transmission of packet data and generates control information indicating the determined values based on forward radio channel quality information of the selected mobile station and the transmission power allocated for the packet data service (Page 4<sup>s</sup>, [0047]).

Therefore it would have been obvious to one of ordinary skill in the art at the time the invention was made to provide Ling et al. with the control information generator taught by Heo et al. since inserting modulation order information aids in the decoding of data by enabling a mobile station to determine a modulation order used by a base station without using a separate mapping table (page 2, [0024]).

Regarding **claim 20**, the combination applied to *claim 19* further teaches-in Heo et al.- wherein the power loader of the adaptive modulators loads the additional information bits based on the channel state information (forward radio channel quality information, Page 4, [0047]).

17. **Claim 22** is rejected under 35 U.S.C. 103(a) as being unpatentable over Ling et al. (US Patent Application Publication 2002/0191703) in view of Onggosanusi et al. (US Patent Application Publication 2002/0114269) as applied to *claim 21* above, and further in view of Hughes-Hartogs (US Patent 4,731,816).

Regarding **claim 22**, Ling et al. disclose everything claimed as applied above (see claim 21), but fail to expressly disclose wherein the constellation selectors of the adaptive modulators insert the additional bits by determining which of the streams of information bits are able to support each of the additional bits with the least required additional power.

Hughes-Hartogs discloses a power allocation system that computes the marginal required power to increase the symbol rate on each carrier from  $n$  to  $n+1$  information units. The system then allocates information units to the carrier that requires the least additional power to increase its symbol rate by one information unit. Because the marginal powers are dependent on the values of the equivalent noise spectrum of the particular established transmission link, the allocation of power and data is specifically tailored to compensate for noise over this particular link (column 3, lines 4-16).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the symbol mapping element of Ling et al. with the power allocation system of Hughes-Hartogs since the resultant allocation of power and data would be tailored to compensate for noise over a particular link.

***Citation of Pertinent Prior Art***

18. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

Walton et al. (US Patent Application Publication 2003/0043732) disclose method and apparatus for a MIMO system using OFDM and selective channel transmission.

Raleigh et al. (US Patent 6,144,711) disclose an information allocation block that makes bit and power assignments to respective channels.

***Conclusion***

Any inquiry concerning this communication or earlier communications from the examiner should be directed to David Huang whose telephone number is (571) 270-1798. The examiner can normally be reached on Monday - Friday, 8:00 a.m. - 5:00 p.m., EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Eliseo Ramos-Feliciano can be reached on (571) 272-7925. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Art Unit: 2609

DSH/dsh

*Lana H. Le*  
4-27-07

LANA LE  
PRIMARY EXAMINER